

TOPSAFE TSL-0-B3 Ø 16 mm	ANCHOR POINT FOR CONCRETE STRUCTURES	TOPSAFE®
LENGTHS: 0 mm	NOTE: ANCHOR POINT WITH CHEMICAL ANCHOR CONCRETE MIN C20/25 SUITABLE FOR MAX 3 PERSONS ANCHOR POINT FOR ABSEILING APPLICATIONS IN ACCORDANCE WITH THE REQUIREMENTS OF THE STANDARD EN 795	WWW.TOPSAFE.CZ WWW.TOPWET.CZ
SCALE: 1:5	CHEMICAL ANCHORAGE DRILL Ø 18mm HOLE DEPTH min. 100 mm CONCRETE THICKNESS TL. min. 140 mm	

BASIC INFORMATION

SPECIFICATIONS	PERSONAL PROTECTION AGAINST FALLS FROM HEIGHT AND TO DEPTH
MATERIAL	STAINLESS STEEL 1.4301
COLOR	STAINLESS STEEL
CERTIFICATION	ACCORDING TO THE STANDARD EN 795:1996
PRODUCER	ABS Safety GmbH

TECHNICAL DATA

PART OF THE SUPPLIED ANCHOR POINT	ANCHOR POINT: - LOOP + THREADED ROD - WASHER
---	---

