

TOPSAFE TSL-BSR10AS Ø42 mm	ANCHOR POINT FOR CONCRETE STRUCTURES	TOPSAFE®
LENGTHS: 350, 500 a 700 mm	NOTE: ANCHORING WITH EXPANSION ANCHORS ANCHOR POINT FOR ABSEILING APPLICATIONS CONCRETE MIN C20/25 DISTRIBUTION PLATE 150x150x8mm AXIAL ANCHOR DISTANCE 110 mm SUITABLE FOR MAX 1 PERSON FOR HORIZONTAL AND VERTICAL USE IN ACCORDANCE WITH THE REQUIREMENTS OF THE STANDARD EN 795	WWW.TOPSAFE.CZ WWW.TOPWET.CZ
SCALE: 1:5	ANCHORING WITH EXPANSION ANCHORS DRILL Ø 12 mm HOLE DEPTH min. 70 mm CONCRETE THICKNESS TL. min. 120 mm	

BASIC INFORMATION

SPECIFICATIONS	PERSONAL PROTECTION AGAINST FALLS FROM HEIGHT AND TO DEPTH
MATERIAL	STAINLESS STEEL 1.4301
COLOR	STAINLESS STEEL
CERTIFICATION	ACCORDING TO THE STANDARD EN 795:2012
PRODUCER	ABS Safety GmbH

TECHNICAL DATA

PART OF THE SUPPLIED ANCHOR POINT	ANCHORING WITH EXPANSION ANCHORS ANCHOR POINT: - LOOP - PLASTIC WASHERS ANCHOR KIT 4x: - EXPANSION ANCHOR - NUT - PAD
ANCHORAGE PARAMETERS	TIGHTENING LOOP 50 Nm TIGHTENING ANCHOR POINT 50 Nm

