

TOPSAFE TSL-360-B	ANCHOR POINT FOR CONCRETE STRUCTURES	TOPSAFE®
LENGTHS: 0 mm	NOTE: ANCHOR POINT WITH CHEMICAL ANCHOR THE EYE OF THE ANCHOR POINT CAN BE ROTATED 360° CONCRETE MIN C20/25 SUITABLE FOR MAX 3 PERSONS ANCHOR POINT FOR ABSEILING APPLICATIONS IN ACCORDANCE WITH THE REQUIREMENTS OF THE STANDARD EN 795	WWW.TOPSAFE.CZ WWW.TOPWET.CZ
SCALE: 1:5	CHEMICAL ANCHORAGE DRILL Ø 18mm HOLE DEPTH min. 90 mm CONCRETE THICKNESS TL. min. 120 mm	

BASIC INFORMATION	
SPECIFICATIONS	PERSONAL PROTECTION AGAINST FALLS FROM HEIGHT AND TO DEPTH
MATERIAL	STAINLESS STEEL 1.4404
COLOR	STAINLESS STEEL, ANCHOR LOOP YELLOW COLOR (RAL 1003)
CERTIFICATION	ACCORDING TO THE STANDARD EN 795:2012
PRODUCER	ABS Safety GmbH

TECHNICAL DATA	
PART OF THE SUPPLIED ANCHOR POINT	ANCHOR POINT: - LOOP + THREADED ROD - WASHER
ANCHORAGE PARAMETERS	TIGHTENING NUT 70 Nm

