

TOPSAFE TSL-360-ST	ANCHOR POINT TO STEEL BEAM	TOPSAFE®
LENGTHS: 0 mm	NOTE: ANCHORING USING A THREADED ROD THE EYE OF THE ANCHOR POINT CAN BE ROTATED 360° DRILL Ø17 mm, FOR HORIZONTAL AND VERTICAL USE SUITABLE FOR MAX 3 PERSONS IN ACCORDANCE WITH THE REQUIREMENTS OF THE STANDARD EN 795	WWW.TOPSAFE.CZ WWW.TOPWET.CZ
SCALE: 1:5		

BASIC INFORMATION

SPECIFICATIONS	PERSONAL PROTECTION AGAINST FALLS FROM HEIGHT AND TO DEPTH
MATERIAL	STAINLESS STEEL 1.4404
COLOR	STAINLESS STEEL, ANCHOR LOOP YELLOW COLOR (RAL 1003)
CERTIFICATION	ACCORDING TO THE STANDARD EN 795:2012
PRODUCER	ABS Safety GmbH

TECHNICAL DATA

PART OF THE SUPPLIED ANCHOR POINT	ANCHOR POINT: - LOOP+ THREADED ROD - STAINLESS STEEL WASHER - VOLCANIC WASHER ANCHOR KIT: - SCREW - PLASTIC WASHER
ANCHORAGE PARAMETERS	TIGHTENING NUT 70 Nm

